



Firmware Version:GE\_1.00

# D-Link®

DPH-150S //	<a href="#">BASIC</a>	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
-------------	-----------------------	---------	------	-------	-------------	----------	--------

<a href="#">Status</a> Wizard Call Log Mmi Set	<b>WAN</b>								
	<table style="width: 100%;"><tr><td style="width: 30%;"><b>Connect Mode:</b></td><td>DHCP</td></tr><tr><td><b>MAC Address:</b></td><td>34:08:04:72:dc:2c</td></tr><tr><td><b>IP Address:</b></td><td>192.168.0.101</td></tr><tr><td><b>Gateway:</b></td><td>192.168.0.1</td></tr></table>	<b>Connect Mode:</b>	DHCP	<b>MAC Address:</b>	34:08:04:72:dc:2c	<b>IP Address:</b>	192.168.0.101	<b>Gateway:</b>	192.168.0.1
<b>Connect Mode:</b>	DHCP								
<b>MAC Address:</b>	34:08:04:72:dc:2c								
<b>IP Address:</b>	192.168.0.101								
<b>Gateway:</b>	192.168.0.1								
	<b>LAN</b>								
	<table style="width: 100%;"><tr><td style="width: 30%;"><b>IP Address:</b></td><td>192.168.10.1</td></tr><tr><td><b>DHCP Server:</b></td><td>ON</td></tr></table>	<b>IP Address:</b>	192.168.10.1	<b>DHCP Server:</b>	ON				
<b>IP Address:</b>	192.168.10.1								
<b>DHCP Server:</b>	ON								
	<b>Phone Number</b>								
	<table style="width: 100%;"><tr><td style="width: 30%;"><b>SIP LINE 1:</b></td><td>@ :5060</td><td style="text-align: right;"><b>Unapplied</b></td></tr><tr><td><b>SIP LINE 2:</b></td><td>@ :5060</td><td style="text-align: right;"><b>Unapplied</b></td></tr></table>	<b>SIP LINE 1:</b>	@ :5060	<b>Unapplied</b>	<b>SIP LINE 2:</b>	@ :5060	<b>Unapplied</b>		
<b>SIP LINE 1:</b>	@ :5060	<b>Unapplied</b>							
<b>SIP LINE 2:</b>	@ :5060	<b>Unapplied</b>							

BROADBAND

Copyright © 2010 D-Link International Pte. Ltd.



DPH-150S //	<a href="#">BASIC</a>	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT						
Status	<b>Network Mode Select</b>												
Wizard	<table> <tr> <td>Static IP MODE</td> <td><input type="radio"/></td> </tr> <tr> <td>DHCP MODE</td> <td><input checked="" type="radio"/></td> </tr> <tr> <td>PPPoE MODE</td> <td><input type="radio"/></td> </tr> </table>							Static IP MODE	<input type="radio"/>	DHCP MODE	<input checked="" type="radio"/>	PPPoE MODE	<input type="radio"/>
Static IP MODE	<input type="radio"/>												
DHCP MODE	<input checked="" type="radio"/>												
PPPoE MODE	<input type="radio"/>												
Call Log	<input type="button" value="BACK"/> <input type="button" value="NEXT"/>												
Mmi Set													
BROADBAND													
Copyright © 2010 D-Link International Pte. Ltd.													



DPH-150S //	<a href="#">BASIC</a>	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT														
Status	<b>Simple SIP Set</b>																				
Wizard	<table> <tr> <td>Display Name</td> <td><input type="text"/></td> </tr> <tr> <td>Server Address</td> <td><input type="text"/></td> </tr> <tr> <td>Server Port</td> <td><input type="text" value="5060"/></td> </tr> <tr> <td>User Name</td> <td><input type="text"/></td> </tr> <tr> <td>Password</td> <td><input type="text"/></td> </tr> <tr> <td>Phone Number</td> <td><input type="text"/></td> </tr> <tr> <td>Enable Register</td> <td><input type="checkbox"/></td> </tr> </table>							Display Name	<input type="text"/>	Server Address	<input type="text"/>	Server Port	<input type="text" value="5060"/>	User Name	<input type="text"/>	Password	<input type="text"/>	Phone Number	<input type="text"/>	Enable Register	<input type="checkbox"/>
Display Name	<input type="text"/>																				
Server Address	<input type="text"/>																				
Server Port	<input type="text" value="5060"/>																				
User Name	<input type="text"/>																				
Password	<input type="text"/>																				
Phone Number	<input type="text"/>																				
Enable Register	<input type="checkbox"/>																				
Call Log	<input type="button" value="BACK"/> <input type="button" value="NEXT"/>																				
Mmi Set																					
BROADBAND																					
Copyright © 2010 D-Link International Pte. Ltd.																					



DPH-150S //	<a href="#">BASIC</a>	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT						
Status	<b>Call information</b>												
Wizard	<table border="1"> <thead> <tr> <th>Start Time</th> <th>Last Time</th> <th>Called Number</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>							Start Time	Last Time	Called Number			
Start Time	Last Time	Called Number											
Call Log													
Mmi Set													
BROADBAND													
Copyright © 2010 D-Link International Pte. Ltd.													



DPH-150S //	<a href="#">BASIC</a>	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT		
Status	<b>Language Selection</b>								
Wizard	<table border="1"> <tr> <td>Language Set:</td> <td>English</td> </tr> </table>							Language Set:	English
Language Set:	English								
Call Log	<table border="1"> <tr> <td>English</td> </tr> <tr> <td>Russian</td> </tr> </table>							English	Russian
English									
Russian									
Mmi Set	<b>Greeting Message Set</b>								
<table border="1"> <tr> <td>Greeting Message:</td> <td>VOIP PHONE</td> </tr> </table>							Greeting Message:	VOIP PHONE	
Greeting Message:	VOIP PHONE								
<input type="button" value="APPLY"/>									
BROADBAND									
Copyright © 2010 D-Link International Pte. Ltd.									



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT										
WAN	<div style="border: 1px solid black; padding: 5px;"> <p><b>WAN Status</b></p> <table border="1"> <tr> <td>Active IP:</td> <td>192.168.0.101</td> </tr> <tr> <td>Current Netmask:</td> <td>255.255.255.0</td> </tr> <tr> <td>Current Gateway:</td> <td>192.168.0.1</td> </tr> <tr> <td>MAC Address:</td> <td>34:08:04:72:dc:2c</td> </tr> <tr> <td>Get MAC Time:</td> <td>20101130</td> </tr> </table> <p><b>WAN Setting</b></p> <p> <input type="radio"/> Static                <input checked="" type="radio"/> DHCP                <input type="radio"/> PPPOE         </p> <p><input checked="" type="checkbox"/> obtain DNS server automatically</p> <p style="text-align: center;"><input type="button" value="APPLY"/></p> </div>							Active IP:	192.168.0.101	Current Netmask:	255.255.255.0	Current Gateway:	192.168.0.1	MAC Address:	34:08:04:72:dc:2c	Get MAC Time:	20101130
Active IP:								192.168.0.101									
Current Netmask:								255.255.255.0									
Current Gateway:								192.168.0.1									
MAC Address:								34:08:04:72:dc:2c									
Get MAC Time:								20101130									
LAN																	
QOS																	
Service Port																	
DHCP Server																	
SNTP Set																	
BROADBAND																	
Copyright © 2010 D-Link International Pte. Ltd.																	



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
WAN	<div style="border: 1px solid black; padding: 5px;"> <p><b>QoS Set</b></p> <p> <input type="checkbox"/> VLAN Enable  <input checked="" type="checkbox"/> VLAN ID Check Enable  <input type="checkbox"/> DiffServ Enable         </p> <p>Voice/Data VLAN differentiated: <input type="text" value="Undifferentiated"/> ▾</p> <p>DiffServ Value: <input type="text" value="0x b8"/></p> <p>Voice 802.1P Priority: <input type="text" value="0"/> (0 - 7)</p> <p>Data 802.1P Priority: <input type="text" value="0"/> (0 - 7)</p> <p>Voice VLAN ID: <input type="text" value="256"/> (0 - 4095)</p> <p>Data VLAN ID: <input type="text" value="254"/> (0 - 4095)</p> <p style="text-align: center;"><input type="button" value="APPLY"/></p> </div>						
LAN							
QOS							
Service Port							
DHCP Server							
SNTP Set							
BROADBAND							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT								
WAN	<div style="border: 1px solid black; padding: 5px;"> <h3>Service Port</h3> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">HTTP Port:</td> <td><input type="text" value="80"/></td> </tr> <tr> <td>Telnet Port:</td> <td><input type="text" value="23"/></td> </tr> <tr> <td>RTP Initial Port:</td> <td><input type="text" value="10000"/></td> </tr> <tr> <td>RTP Port Quantity:</td> <td><input type="text" value="200"/></td> </tr> </table> <p style="text-align: center;"><input type="button" value="APPLY"/></p> <p style="text-align: center;">If modify HTTP or Telnet port,you'd better set it more than 1024,then restart.</p> </div>							HTTP Port:	<input type="text" value="80"/>	Telnet Port:	<input type="text" value="23"/>	RTP Initial Port:	<input type="text" value="10000"/>	RTP Port Quantity:	<input type="text" value="200"/>
HTTP Port:								<input type="text" value="80"/>							
Telnet Port:								<input type="text" value="23"/>							
RTP Initial Port:								<input type="text" value="10000"/>							
RTP Port Quantity:								<input type="text" value="200"/>							
LAN															
QOS															
Service Port															
DHCP Server															
SNTP Set															
BROADBAND															
Copyright © 2010 D-Link International Pte. Ltd.															



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT																																				
WAN	<div style="border: 1px solid black; padding: 5px;"> <h3>DHCP Leased Table</h3> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 60%;">Leased IP Address</th> <th>Client Hardware Address</th> </tr> </table> <h3>DHCP Lease Table</h3> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Name</th> <th>Start IP</th> <th>End IP</th> <th>Lease Time</th> <th>Netmask</th> <th>Gateway</th> <th>DNS</th> </tr> </thead> <tbody> <tr> <td>lan</td> <td>192.168.10.1</td> <td>192.168.10.30</td> <td>1440</td> <td>255.255.255.0</td> <td>192.168.10.1</td> <td>192.168.10.1</td> </tr> </tbody> </table> <h3>DHCP Lease Table Setting</h3> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Lease Table Name:</td> <td><input type="text"/></td> </tr> <tr> <td>Start IP:</td> <td><input type="text"/></td> </tr> <tr> <td>End IP:</td> <td><input type="text"/></td> </tr> <tr> <td>Lease Time:</td> <td><input type="text"/> (minute)</td> </tr> <tr> <td>Netmask:</td> <td><input type="text"/></td> </tr> <tr> <td>Gateway:</td> <td><input type="text"/></td> </tr> <tr> <td>DNS:</td> <td><input type="text"/></td> </tr> </table> <p style="text-align: center;"><input type="button" value="Add"/></p> <h3>DHCP Lease Table Delete</h3> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">Lease Table Name:</td> <td><input type="text" value="lan"/></td> <td><input type="button" value="Delete"/></td> </tr> </table> <h3>DNS relay Setting</h3> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;">DNS Relay:</td> <td><input checked="" type="checkbox"/></td> <td><input type="button" value="APPLY"/></td> </tr> </table> </div>							Leased IP Address	Client Hardware Address	Name	Start IP	End IP	Lease Time	Netmask	Gateway	DNS	lan	192.168.10.1	192.168.10.30	1440	255.255.255.0	192.168.10.1	192.168.10.1	Lease Table Name:	<input type="text"/>	Start IP:	<input type="text"/>	End IP:	<input type="text"/>	Lease Time:	<input type="text"/> (minute)	Netmask:	<input type="text"/>	Gateway:	<input type="text"/>	DNS:	<input type="text"/>	Lease Table Name:	<input type="text" value="lan"/>	<input type="button" value="Delete"/>	DNS Relay:	<input checked="" type="checkbox"/>	<input type="button" value="APPLY"/>
Leased IP Address								Client Hardware Address																																			
Name								Start IP	End IP	Lease Time	Netmask	Gateway	DNS																														
lan								192.168.10.1	192.168.10.30	1440	255.255.255.0	192.168.10.1	192.168.10.1																														
Lease Table Name:								<input type="text"/>																																			
Start IP:								<input type="text"/>																																			
End IP:								<input type="text"/>																																			
Lease Time:	<input type="text"/> (minute)																																										
Netmask:	<input type="text"/>																																										
Gateway:	<input type="text"/>																																										
DNS:	<input type="text"/>																																										
Lease Table Name:	<input type="text" value="lan"/>	<input type="button" value="Delete"/>																																									
DNS Relay:	<input checked="" type="checkbox"/>	<input type="button" value="APPLY"/>																																									
LAN																																											
QOS																																											
Service Port																																											
DHCP Server																																											
SNTP Set																																											
BROADBAND																																											
Copyright © 2010 D-Link International Pte. Ltd.																																											



DPH-150S // BASIC NETWORK VOIP PHONE MAINTENANCE SECURITY LOGOUT

WAN

LAN

QOS

Service Port

DHCP Server

SNTP Set

### SNTP Time Set

Server:

Time Zone:

Time Out:  (seconds)

12 Hours Systems:

SNTP:

**APPLY**

### Daylight Timeset

Enable Daylight:

Time shift (minutes):

Time Zone	Start Date	End Date
Month: <input type="text" value="March"/>	<input type="text" value="March"/>	<input type="text" value="October"/>
Week: <input type="text" value="5"/>	<input type="text" value="5"/>	<input type="text" value="5"/>
Day: <input type="text" value="Sunday"/>	<input type="text" value="Sunday"/>	<input type="text" value="Sunday"/>
Hour: <input type="text" value="2"/>	<input type="text" value="2"/>	<input type="text" value="2"/>
Minute: <input type="text" value="0"/>	<input type="text" value="0"/>	<input type="text" value="0"/>

**APPLY**

### Manual Timeset

Year:

Months:

Day:

Hour:

Minute:

**APPLY**

BROADBAND



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
WAN	<b>SIP Line Select</b>						
LAN	<div style="display: flex; align-items: center;"> <div style="border: 1px solid black; padding: 2px;">SIP 1</div> <div style="margin-left: 20px;">Load</div> </div>						
QOS	<b>SIP 2</b>						
Service Port	<b>Basic Setting</b>						
DHCP Server	Register Status: <b>Unapplied</b>			Display Name: <input type="text"/>			
SNTP Set	Server Name: <input type="text"/>			Proxy Server Address: <input type="text"/>			
	Server Address: <input type="text"/>			Proxy Server Port: <input type="text"/>			
	Server Port: <input type="text" value="5060"/>			Proxy Username: <input type="text"/>			
	Account Name: <input type="text"/>			Proxy Password: <input type="text"/>			
	Password: <input type="text"/>			Domain Realm: <input type="text"/>			
	Phone Number: <input type="text"/>			Enable Register: <input type="checkbox"/>			
	<div style="display: flex; justify-content: center; gap: 10px;"> <div>APPLY</div> <div>Advanced Set</div> </div>						
<b>BROADBAND</b>							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
WAN	<b>LAN Set</b>						
LAN	LAN IP: <input type="text" value="192.168.10.1"/>						
QOS	Netmask: <input type="text" value="255.255.255.0"/>						
Service Port	DHCP Service: <input checked="" type="checkbox"/>						
DHCP Server	NAT: <input checked="" type="checkbox"/>						
SNTP Set	Bridge Mode: <input type="checkbox"/>						
	<div style="display: flex; justify-content: center; gap: 10px;"> <div>APPLY</div> </div>						
<b>BROADBAND</b>							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
DSP	<b>DSP Configuration</b>						
Call Service	First Codec:	<input type="text" value="g711Ulaw64k"/>	Second Codec:	<input type="text" value="g711Alaw64k"/>			
Digital Map	Third Codec:	<input type="text" value="g729"/>	Fourth Codec:	<input type="text" value="g723"/>			
Phone Book	Fifth Codec:	<input type="text" value="g711Alaw64k"/>	Sixth Codec:	<input type="text" value="g711Alaw64k"/>			
Function Key	Handdown Time:	<input type="text" value="200"/> ms	Default Ring Type:	<input type="text" value="Type 1"/>			
	Input Volume:	<input type="text" value="3"/> (1-9)	Output Volume:	<input type="text" value="5"/> (1-9)			
	Handfree Volume:	<input type="text" value="5"/> (1-9)	Ring Volume:	<input type="text" value="5"/> (1-9)			
	G729 Payload Length:	<input type="text" value="20ms"/>	Signal Standard:	<input type="text" value="China"/>			
	G722 Timestamps:	<input type="text" value="160/20ms"/>	G723 Bit Rate:	<input type="text" value="6.3kb/s"/>			
	VAD:	<input type="checkbox"/>	Dtmf Payload Type:	<input type="text" value="101"/> (96-127)			
	<input type="button" value="APPLY"/>						
<b>BROADBAND</b>							
Copyright © 2010 D-Link International Pte. Ltd.							

<b>DSP Configuration</b>							
First Codec:	<input type="text" value="g711Ulaw64k"/>	Second Codec:	<input type="text" value="g711Alaw64k"/>				
Third Codec:	<input type="text" value="g711Alaw64k"/>	Fourth Codec:	<input type="text" value="g723"/>				
Fifth Codec:	<input type="text" value="g711Ulaw64k"/>	Sixth Codec:	<input type="text" value="g711Alaw64k"/>				
Handdown Time:	<input type="text" value="None"/>	Default Ring Type:	<input type="text" value="Type 1"/>				
Input Volume:	<input type="text" value="3"/> (1-9)	Output Volume:	<input type="text" value="5"/> (1-9)				
Handfree Volume:	<input type="text" value="5"/> (1-9)	Ring Volume:	<input type="text" value="5"/> (1-9)				
G729 Payload Length:	<input type="text" value="20ms"/>	Signal Standard:	<input type="text" value="China"/>				
G722 Timestamps:	<input type="text" value="160/20ms"/>	G723 Bit Rate:	<input type="text" value="6.3kb/s"/>				
VAD:	<input type="checkbox"/>	Dtmf Payload Type:	<input type="text" value="101"/> (96-127)				
<input type="button" value="APPLY"/>							



## DSP Configuration

First Codec:	<input type="text" value="g711Ulaw64k"/>	Second Codec:	<input type="text" value="g711Alaw64k"/>
Third Codec:	<input type="text" value="g729"/>	Fourth Codec:	<input type="text" value="g723"/>
Fifth Codec:	<input type="text" value="g711Alaw64k"/>	Sixth Codec:	<input type="text" value="g711Alaw64k"/>
Handdown Time:	<input type="text" value="200"/> ms	Default Ring Type:	<input type="text" value="Type 1"/>
Input Volume:	<input type="text" value="3"/> (1-9)	Output Volume:	<input type="text" value="5"/> (1-9)
Handfree Volume:	<input type="text" value="5"/> (1-9)	Ring Volume:	<input type="text" value="5"/> (1-9)
G729 Payload Length:	<input type="text" value="20ms"/>	Signal Standard:	<input type="text" value="China"/>
G722 Timestamps:	<input type="text" value="20ms"/>	G723 Bit Rate:	<input type="text" value="6.3kb/s"/>
VAD:	<input type="text" value=""/>	Dtmf Payload Type:	<input type="text" value="101"/> (96-127)

## DSP Configuration

First Codec:	<input type="text" value="g711Ulaw64k"/>	Second Codec:	<input type="text" value="g711Alaw64k"/>
Third Codec:	<input type="text" value="g729"/>	Fourth Codec:	<input type="text" value="g723"/>
Fifth Codec:	<input type="text" value="g711Alaw64k"/>	Sixth Codec:	<input type="text" value="g711Alaw64k"/>
Handdown Time:	<input type="text" value="200"/> ms	Default Ring Type:	<input type="text" value="Type 1"/>
Input Volume:	<input type="text" value="3"/> (1-9)	Output Volume:	<input type="text" value="5"/> (1-9)
Handfree Volume:	<input type="text" value="5"/> (1-9)	Ring Volume:	<input type="text" value="5"/> (1-9)
G729 Payload Length:	<input type="text" value="20ms"/>	Signal Standard:	<input type="text" value="China"/>
G722 Timestamps:	<input type="text" value="160/20ms"/>	G723 Bit Rate:	<input type="text" value="6.3kb/s"/>
VAD:	<input type="text" value=""/>	Dtmf Payload Type:	<input type="text" value="101"/> (96-127)

Firmware Version:GE\_1.00



DPH-150S // BASIC NETWORK VOIP PHONE MAINTENANCE SECURITY LOGOUT

- DSP
- Call Service**
- Digital Map
- Phone Book
- Function Key

### Call Service Setting

Hot Line:	<input type="text"/>	No Answer Time:	<input type="text" value="20"/> (seconds)
P2P IP Prefix:	<input type="text"/>	Auto Answer:	<input type="checkbox"/>
Do Not Disturb:	<input type="checkbox"/>	Ban Outgoing:	<input type="checkbox"/>
Enable Call Transfer:	<input checked="" type="checkbox"/>	Enable Call Waiting:	<input checked="" type="checkbox"/>
Enable Three Way Call:	<input checked="" type="checkbox"/>	Accept Any Call:	<input checked="" type="checkbox"/>
Enable Auto Handdown:	<input type="checkbox"/>	XML Server:	<input type="text"/>

### Black List

<input type="text"/>	<input type="button" value="Add"/>	<input type="text"/>	<input type="button" value="Delete"/>
----------------------	------------------------------------	----------------------	---------------------------------------

### Limit List

<input type="text"/>	<input type="button" value="Add"/>	<input type="text"/>	<input type="button" value="Delete"/>
----------------------	------------------------------------	----------------------	---------------------------------------

BROADBAND



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
DSP	<b>Digital Map Set</b>						
Call Service	<input checked="" type="checkbox"/> End With "#"						
Digital Map	<input type="checkbox"/> Fixed Length <input type="text" value="11"/>						
Phone Book	<input checked="" type="checkbox"/> Time Out <input type="text" value="5"/> (3--30)						
Function Key	<input type="button" value="APPLY"/>						
	<b>Digital Rule table</b>						
	Rules:						
	<input type="text"/>	<input type="button" value="Add"/>	<input type="button" value="v"/>	<input type="button" value="Del"/>			
BROADBAND							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT								
DSP	<b>Phonebook Table</b>														
Call Service	<table border="1"> <thead> <tr> <th>Index</th> <th>Name</th> <th>Number</th> <th>Type</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table>							Index	Name	Number	Type				
Index	Name	Number	Type												
Digital Map	<b>Add Phone Book</b>														
Phone Book	Name: <input type="text"/>														
Function Key	Number: <input type="text"/> <input type="button" value="Add"/>														
	Ring Type: <input type="button" value="Default"/> <input type="button" value="v"/>														
	<b>Phone Book Option</b>														
	<input type="button" value="v"/> <input type="button" value="Delete"/> <input type="button" value="Modify"/>														
BROADBAND															
Copyright © 2010 D-Link International Pte. Ltd.															



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
DSP	<b>Interface Configuration</b>						
Call Service	Contrast: <input type="text" value="4"/> (1-9)		Luminance: <input type="text" value="1"/> (0-1)				
Digital Map	MWI Number: <input type="text"/>						
Phone Book	<input type="button" value="APPLY"/>						
Function Key	<b>Function Key Setting</b>						
	F 1	Key Event <input type="text" value="Key Event"/>	<input type="text" value="F_MWI"/>				
		<ul style="list-style-type: none"> <li>None</li> <li>Memory Key</li> <li>Line</li> <li>Key Event</li> <li>Dtmf</li> </ul>	<input type="button" value="APPLY"/>				
BROADBAND							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
Autoprovision	<b>Auto Update Setting</b>						
SYSLOG	Current Config Version: 2.0002						
Config	Server Address: <input type="text" value="0.0.0.0"/>						
Update	Username: <input type="text" value="user"/>						
Account Set	Password: <input type="password" value="...."/>						
Reboot	Config File Name: <input type="text"/>						
	Config Encrypt Key: <input type="text"/>						
	Protocol Type: <input type="text" value="FTP"/>						
	Update Interval Time: <input type="text" value="1"/> Hour						
	Update Mode: <input type="text" value="Disable"/>						
	Enable DHCP Option 66: <input type="checkbox"/>						
	<input type="button" value="APPLY"/>						
BROADBAND							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S // BASIC NETWORK VOIP PHONE MAINTENANCE SECURITY LOGOUT

Autoprovision

SYSLOG

Config

Update

Account Set

Reboot

### Syslog Set

Server IP: 0.0.0.0

Server Port: 514

MGR Log Level: None

SIP Log Level: None

Enable Syslog:

APP

- None
- Alert
- Critical
- Error
- Warning
- Notice
- Info
- Debug

BROADBAND

Copyright © 2010 D-Link International Pte. Ltd.



DPH-150S // BASIC NETWORK VOIP PHONE MAINTENANCE SECURITY LOGOUT

Autoprovision

SYSLOG

Config

Update

Account Set

Reboot

### Syslog Set

Server IP: 0.0.0.0

Server Port: 514

MGR Log Level: None

SIP Log Level: None

Enable Syslog:

APP

- None
- Alert
- Critical
- Error
- Warning
- Notice
- Info
- Debug

BROADBAND

Copyright © 2010 D-Link International Pte. Ltd.



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
Autoprovision	<b>Save Configuration</b>						
SYSLOG	Press the "Save" button to save the configuration files !						
Config	<input type="button" value="Save"/>						
Update	<b>Backup Config</b>						
Account Set	Save all Network and VoIP settings.						
Reboot	<a href="#">Right Click here to Save as Config File (.txt)</a>						
	<b>Clear Configuration</b>						
	Press the "Reset" button to Reset the configuration files !						
	<input type="button" value="Reset"/>						
BROADBAND							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
Autoprovision	<b>Web Update</b>						
SYSLOG	Select file <input type="text"/> <input type="button" value="Обзор..."/> (*.z,*.txt,*.au,*.wav) <input type="button" value="Update"/>						
Config	<b>FTP Update</b>						
Update	Server:	<input type="text"/>					
Account Set	Username:	<input type="text"/>					
Reboot	Password:	<input type="text"/>					
	File Name:	<input type="text"/>					
	Type:	Application update ▾					
	Protocol:	FTP ▾					
	<input type="button" value="APPLY"/>						
BROADBAND							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT						
Autoprovision	<b>Set Keyboard Password</b>												
SYSLOG	Keyboard Password <input type="password"/>						<input type="button" value="Set"/>						
Config	<b>User Set</b>												
Update	<table border="1"> <thead> <tr> <th>User Name</th> <th>User Level</th> </tr> </thead> <tbody> <tr> <td>admin</td> <td>Root</td> </tr> <tr> <td>guest</td> <td>General</td> </tr> </tbody> </table>							User Name	User Level	admin	Root	guest	General
User Name	User Level												
admin	Root												
guest	General												
Account Set	<b>Add User</b>												
Reboot	User Name: <input type="text"/> User Level: <input type="text" value="Root"/> Password: <input type="text"/> Confirm: <input type="text"/>						<input type="button" value="Submit"/>						
	<b>Account Option</b>												
	admin <input type="button" value="Delete"/>						<input type="button" value="Modify"/>						

BROADBAND

Copyright © 2010 D-Link International Pte. Ltd.



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
Autoprovision	<b>Reboot Phone</b>						
SYSLOG	Press the "Reboot" button to reboot Phone !						
Config	<input type="button" value="Reboot"/>						
Update							
Account Set							
Reboot							

BROADBAND

Copyright © 2010 D-Link International Pte. Ltd.



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
MMI Filter	<b>MMI Filter Table</b>						
Firewall	Start IP		End IP		Option		
NAT	<b>MMI Filter Table Set</b>						
VPN	Start IP:	<input type="text"/>	End IP:	<input type="text"/>	<input type="button" value="Add"/>		
	<b>MMI Filter Table Set</b>						
	<input type="checkbox"/> MMI Filter			<input type="button" value="APPLY"/>			
BROADBAND							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S //	BASIC	NETWORK	VOIP	PHONE	MAINTENANCE	SECURITY	LOGOUT
MMI Filter	<b>Firewall Type</b>						
Firewall	<input type="checkbox"/> In_access Enable			<input type="checkbox"/> Out_access Enable			
NAT	<input type="button" value="APPLY"/>						
VPN	<b>Firewall Input Rule Table</b>						
	Index Deny/Permit	Protocol	Src Addr	Src Mask	Des Addr	Des Mask	Range Port
	<b>Firewall Output Rule Table</b>						
	Index Deny/Permit	Protocol	Src Addr	Src Mask	Des Addr	Des Mask	Range Port
	<b>Firewall Set</b>						
	Input/Output:	<input type="text" value="Input"/>	Src Addr:	<input type="text"/>			
	Deny/Permit:	<input type="text" value="Deny"/>	Des Addr:	<input type="text"/>	<input type="button" value="Add"/>		
	Protocol Type:	<input type="text" value="UDP"/>	Src Mask:	<input type="text"/>			
	Port Range:	<input type="text" value="more than"/>	Des Mask:	<input type="text"/>			
	<b>Rule Delete</b>						
	Input/Output:	<input type="text" value="Input"/>	Index To Be Deleted:	<input type="text"/>	<input type="button" value="Delete"/>		
BROADBAND							
Copyright © 2010 D-Link International Pte. Ltd.							



DPH-150S // BASIC NETWORK VOIP PHONE MAINTENANCE SECURITY LOGOUT

MMI Filter

Firewall

NAT

VPN

### Protocol Set

 IPSec ALG FTP ALG PPTP ALG

### NAT Table

Inside IP	Inside TCP Port	Outside TCP Port

Inside IP	Inside UDP Port	Outside UDP Port

### NAT Table Option

Transfer Type: Outside Port: Inside IP: Inside Port: 




BROADBAND

Copyright © 2010 D-Link International Pte. Ltd.



DPH-150S // BASIC NETWORK VOIP PHONE MAINTENANCE SECURITY LOGOUT

MMI Filter

Firewall

NAT

VPN

### VPN IP

### VPN Mode

 L2TP Enable VPN

### L2TP

VPN Server Addr: VPN User Name: VPN Password : 


BROADBAND

Copyright © 2010 D-Link International Pte. Ltd.





DPH-150S //	ОСНОВНОЕ	СЕТЬ	VOIP	ТЕЛЕФОН	ОБСЛУЖИВАНИЕ	БЕЗОПАСНОСТЬ	ВЫХОД															
Статус	<table border="1"> <thead> <tr> <th colspan="3">WAN</th> </tr> </thead> <tbody> <tr> <td>Режим соединения:</td> <td colspan="2">DHCP</td> </tr> <tr> <td>MAC-адрес:</td> <td colspan="2">34:08:04:72:dc:2c</td> </tr> <tr> <td>IP-адрес:</td> <td colspan="2">192.168.0.101</td> </tr> <tr> <td>Шлюз:</td> <td colspan="2">192.168.0.1</td> </tr> </tbody> </table>							WAN			Режим соединения:	DHCP		MAC-адрес:	34:08:04:72:dc:2c		IP-адрес:	192.168.0.101		Шлюз:	192.168.0.1	
WAN																						
Режим соединения:								DHCP														
MAC-адрес:								34:08:04:72:dc:2c														
IP-адрес:	192.168.0.101																					
Шлюз:	192.168.0.1																					
Мастер																						
Журнал вызовов																						
Настройка MMI																						
	<table border="1"> <thead> <tr> <th colspan="3">LAN</th> </tr> </thead> <tbody> <tr> <td>IP-адрес:</td> <td colspan="2">192.168.10.1</td> </tr> <tr> <td>DHCP-сервер:</td> <td colspan="2">ВКЛ</td> </tr> </tbody> </table>							LAN			IP-адрес:	192.168.10.1		DHCP-сервер:	ВКЛ							
LAN																						
IP-адрес:	192.168.10.1																					
DHCP-сервер:	ВКЛ																					
	<table border="1"> <thead> <tr> <th colspan="3">Номер телефона</th> </tr> </thead> <tbody> <tr> <td>SIP-ЛИНИЯ 1:</td> <td>@ :5060</td> <td>Не используется</td> </tr> <tr> <td>SIP-ЛИНИЯ 2:</td> <td>@ :5060</td> <td>Не используется</td> </tr> </tbody> </table>							Номер телефона			SIP-ЛИНИЯ 1:	@ :5060	Не используется	SIP-ЛИНИЯ 2:	@ :5060	Не используется						
Номер телефона																						
SIP-ЛИНИЯ 1:	@ :5060	Не используется																				
SIP-ЛИНИЯ 2:	@ :5060	Не используется																				
BROADBAND																						
Copyright © 2010 D-Link International Pte. Ltd.																						

Использование материала возможно, только с указанием ссылок на ресурсы [dlink-help.ru](http://dlink-help.ru) и [it-platform.ru](http://it-platform.ru)